

## Technical Specification

### Ventilation Modes

A/O-V with sigh	A/O-P
SIMV-V	SIMV-P

### Parameters

• Tidal Volume:	0~2000 ml
• Respiration Rate:	1~120 bpm (A/O mode) 1~40 bpm (SIMV mode)
• I:E Ratio:	1:10~4:1
• FiO <sub>2</sub> :	40%~100%
• Trigger Sensitivity:	Pressure trigger: -20~0 cmH <sub>2</sub> O
• Flow Trigger:	2~30 L/min
• PEEP:	0~30 cmH <sub>2</sub> O

### Monitoring

• Pressure Value:	Ppeak, PEEP
• Volume / Flow Value:	Vt, MV
• Time Value:	ftotal
• Real Time Curves:	Pressure-Time, Flow-time

### Alarms

Paw high	Paw low	MV high	Gas supply down
No VT	FiO <sub>2</sub> high	FiO <sub>2</sub> low	Apnea
Continuous pressure high / OP high		EX. power lost	
O <sub>2</sub> deficiency	Battery low		

### Technical Data

• Supply Gas:	O <sub>2</sub> , 0.25~0.6 MPa
• Power Supply:	AC100~240 V, 50 Hz/60 Hz, ≤66 VA
• Screen Size:	5" LOD Screen
• Maximum Security Pressure:	≤8 KPa
• Compliance:	≤4 ml /100 Pa
• Dimension (WxDxH):	168 mm x 166 mm x 300 mm
• Battery Operating Time:	Approx. 4.5H
• Weight:	3.2 kg (Main unit) 8 kg (Main unit & Accessories)

Remark: Above configurations include standard and optional. Please check price with your Aeonmed sales representative.



CE 0123

**AEOMED**  
Reliable Quality Thoughtful Service

HO: Building 9, No.26 Outer Ring West Road, Fengtai District, Beijing 100070, China  
 Science Park: No. 10, Chabai Street, Yanjiao Development Zone, Sanhe City, Hebei Province  
 085201, China  
 TEL: +86-10-8841 1128 FAX: +86-10-8871 8089  
 Http://www.aeonmed.com E-mail: marketing@aeonmed.com

The information contained in this leaflet is correct at the date of publication. The policy of Beijing Aeonmed Co., Ltd. is one of the continued improvement to its products. Because of this policy, Aeonmed reserves the right to make any change, which may affect the information in this leaflet without giving prior notice. 017004-002

**AEOMED**  
Reliable Quality Thoughtful Service



### Multi-functional Emergency Transport Ventilator

- It helps optimize quality of care & patient comfort, improving patient outcomes
- One device addresses diverse ventilation requirements, fully covering various situations

- Combines advanced technology and versatile ventilation functions
- Meets the breathing requirements of adults, pediatric and infant patients
- Pneumatically driven electronically controlled

### Integrated with Versatile Ventilation Modes

- Pressure control & Volume control mode
- Invasive & Non-Invasive ventilation
- SPONT/PSV, CPAP modes

### Manual Intervention Functions

- Manual breath
- Inspiratory hold

### Enhancements

- FiO<sub>2</sub> 40% to 100% continuously adjustable
- Waveform display: Pressure-time, Flow-time
- Alarm silence
- Pre-use test

### Features

Simple operation, compact design, reliable performance



- Waveform display and multi-parameter monitoring
- Electronically controlled PEEP



- Acoustic and visual alarms
- Anti-crash design



- Direct access to critical settings and patient data



- Operate with low flow oxygen supply

### Safety Guarantee

- Meets with EN1789 standard
- IPX4 waterproof level

### Applications

Emergency – Transport – Intra-hospital transfer – Recovery



### Multiple Ways of Power Supply

- Vehicle D/C power
- 4.5h long lasting internal battery
- A/C power adaptor
- External backup battery(optional)

### Comprehensive Accessories

- Suction unit
- Hanging plate assembly
- 2.8L Oxygen cylinder kit
- Bluetooth module
- Oxygen sensor